

CONICAL PAILS

Optimised transport and storage space thanks to its conical shape
Triple seaming for higher UN approval standards
2 standard closing systems available: crimp lid and ring and latch lid
Standard use: paints and coatings, adhesives, resins, inks, chemical products in general
Automatic TOPLock closing system for ring & latch lids available in several formats





Format	Filling vol. (l)	Brimful capac. (l)	Diam. bottom a) (mm)	Diam. lid b) (mm)	Height h) (mm)	Handle	Tactile	Triple seam.	Crimp lid (1)	Approval	Ring & Latch lid (2)	Approval	Ring types	Remarks
D 160 x 140	2	2,2	148	160	140	1	O				Y	UN / RID/ADR	NOR, STO, S-R	
D 160 x 163	2,5	2,7	148	160	163	1	O				Y	UN / RID/ADR	NOR, STO, S-R	
D 160 x 200	3	3,4	148	160	200	1	O				Y	UN / RID/ADR	NOR, STO, S-R	
D 160 x 245	4,1	4,2	148	160	245	1	O				Y	UN / RID/ADR	NOR, STO, S-R	
D 180 x 170	3	3,6	165	180	170	1	O	Y	Y	UN	Y	UN	NOR	
D 180 x 195	4	4,3	165	180	195	1	O	Y	Y	UN	Y	UN	NOR	
D 180 x 215	4,5	4,9	165	180	215	1	O	Y	Y	UN	Y	UN	NOR	
D 180 x 235	5	5,3	165	180	235	1	O	Y	Y	UN	Y	UN	NOR	
D 180 x 255	5,5	5,9	165	180	255	1	O	Y	Y	UN	Y	UN	NOR	
D 180 x 275	6	6,5	165	180	275	1	O	Y	Y	UN	Y	UN	NOR	
D 180 x 290	6/6,5	6,9	165	180	290	1	O	Y	Y	UN	Y	UN	NOR	
D 200 x 158	4	4,1	188	200	158	1	O				Y	UN / RID/ADR	NOR, STO, S-R, TPK	
D 200 x 173	4,5	4,5	188	200	173	1	O				Y	UN / RID/ADR	NOR, STO, S-R, TPK	
D 200 x 184	4,5	4,7	188	200	184	1	O				Y	UN / RID/ADR	NOR, STO, S-R, TPK	
D 200 x 209	5,4	5,7	188	200	209	1	O				Y	UN / RID/ADR	NOR, STO, S-R, TPK	
D 200 x 221	6	6,0	188	200	221	1	O				Y	UN / RID/ADR	NOR, STO, S-R, TPK	
D 200 x 255	7	7,0	188	200	255	1	O				Y	UN / RID/ADR	NOR, STO, S-R, TPK	
D 230 x 150	4,5	4,8	217	230	150	1	O	Y			Y	UN / RID/ADR	NOR, STO, S-R, TPK	
D 230 x 170	5,4	5,7	217	230	170	1	O	Y			Y	UN / RID/ADR	NOR, STO, S-R, TPK	
D 230 x 190	6	6,4	217	230	190	1	O	Y			Y	UN / RID/ADR	NOR, STO, S-R, TPK	
D 230 x 210	7	7,2	217	230	210	1	O	Y			Y	UN / RID/ADR	NOR, STO, S-R, TPK	
D 230 x 250	8	8,8	217	230	250	1	O	Y			Y	UN / RID/ADR	NOR, STO, S-R, TPK	
D 230 x 290	10	10,5	217	230	290	1	O	Y			Y	UN / RID/ADR	NOR, STO, S-R, TPK	
D 230 x 310	11	11,2	217	230	310	1	O	Y			Y	UN / RID/ADR	NOR, STO, S-R, TPK	
D 230 x 327	12	11,9	217	230	327	1	O	Y			Y	UN / RID/ADR	NOR, STO, S-R, TPK	
D 230 x 350	12,5	12,8	217	230	350	1	O	Y			Y	UN / RID/ADR	NOR, STO, S-R, TPK	
D 230 x 380	14	14,1	217	230	380	1	O	Y			Y	UN / RID/ADR	NOR, STO, S-R, TPK	
D 240 x 211	7	8,2	223	240	211	1			Y					
D 240 x 232	8	9,1	223	240	232	1			Y					
D 240 x 271	10	10,7	223	240	271	1			Y					
D 285 x 216 L	10	12,0	267	285	216	1			Y					
D 285 x 240 L	12,5	14,1	267	285	240	1			Y					
D 285 x 280 L	14	16,1	267	285	280	1			Y					
D 285 x 300 L	15	17,1	267	285	300	1			Y					
D 285 x 320 L	16	18,3	267	285	320	1			Y					
D 285 x 335 L	18	19,4	267	285	335	1			Y					
D 285 x 370 L	20	21,3	267	285	370	1			Y					

O - Optional

Ring types

NOR	Standard clamping ring
STO	Störing
S-R	S-Ring
TPK	TOPLock ring

Remarks:

1) UN approval with formliner available
2) Sheet thickness 0,45mm

CONICAL PAILS

Format	Filling vol. (l)	Brimful capac. (l)	Diam. bottom a) (mm)	Diam. lid b) (mm)	Height h) (mm)	Handle	Tactile	Triple seam.	Crimp lid (1)	Approval	Ring & Latch lid (2)	Approval	Ring types	Remarks
D 285 x 216	10	11,9	267	285	216	1		Y	Y	UN / RID/ADR	Y	UN	NOR, TPK	1)
D 285 x 248	12,5	13,8	267	285	248	1		Y	Y	UN / RID/ADR	Y	UN	NOR, TPK	1)
D 285 x 280	14	15,8	267	285	280	1		Y	Y	UN / RID/ADR	Y	UN	NOR, TPK	1)
D 285 x 300	15	16,8	267	285	300	1		Y	Y	UN / RID/ADR	Y	UN	NOR, TPK	1)
D 285 x 320	16	18,0	267	285	320	1		Y	Y	UN / RID/ADR	Y	UN	NOR, TPK	1)
D 285 x 335	18	19,1	267	285	335	1		Y	Y	UN / RID/ADR	Y	UN	NOR, TPK	1)
D 285 x 370	20	21,0	267	285	370	1		Y	Y	UN / RID/ADR	Y	UN	NOR, TPK	1)
D 285 x 382	20	22,0	267	285	382	1		Y	Y	UN / RID/ADR	Y	UN	NOR, TPK	1)
D 285 x 392	22	22,5	267	285	392	1		Y	Y	UN / RID/ADR	Y	UN	NOR, TPK	1)
D 285 x 430	22	25,3	267	285	430	1		Y	Y	UN / RID/ADR	Y	UN	NOR, TPK	1)
D 285 x 454	25	26,3	267	285	454	1		Y	Y	UN / RID/ADR	Y	UN	NOR	
D 285 x 467	25	27,1	267	285	467	1		Y	Y	UN / RID/ADR	Y	UN	NOR	
D 285 x 320 045	16	18,0	267	285	320	1		Y	Y	UN	Y	UN	NOR	2)
D 285 x 335 045	18	19,1	267	285	335	1		Y	Y	UN	Y	UN	NOR	2)
D 285 x 382 045	20	22,0	267	285	382	1		Y	Y	UN	Y	UN	NOR	2)
D 285 x 454 045	25	26,3	267	285	454	1		Y	Y	UN	Y	UN	NOR	2)
D 286 x 240	11	14,1	272	286	240	1	O	Y	Y		Y		NOR	
D 286 x 260	12	15,3	272	286	260	1	O	Y	Y		Y		NOR	
D 286 x 300	15	17,8	272	286	300	1	O	Y	Y		Y		NOR	
D 286 x 320	16	19,0	272	286	320	1	O	Y	Y		Y		NOR	
D 286 x 370	20	22,2	272	286	370	1	O	Y	Y		Y		NOR	
D 292 x 230 L	12,5	14,1	267	292	230	1			Y					
D 292 x 276 L	14	15,8	267	292	276	1			Y					
D 292 x 296 L	15	18,2	267	292	296	1			Y					
D 292 x 331 L	18	21,5	267	292	331	1			Y					
D 292 x 366 L	20	23,7	267	292	366	1			Y					
D 292 x 378 L	22	24,8	267	292	378	1			Y					
D 292 x 414 L	22	25,5	267	292	414	1			Y					
D 292 x 440 L	25	26,2	267	292	440	1			Y					
D 292 x 230	12,5	14,1	267	292	230	1		Y	Y	UN / RID/ADR				
D 292 x 276	14	15,8	267	292	276	1		Y	Y	UN / RID/ADR				
D 292 x 296	15	18,2	267	292	296	1		Y	Y	UN / RID/ADR				
D 292 x 331	18	21,5	267	292	331	1		Y	Y	UN / RID/ADR				
D 292 x 366	20	23,7	267	292	366	1		Y	Y	UN / RID/ADR				
D 292 x 378	21	24,8	267	292	378	1		Y	Y	UN / RID/ADR				
D 292 x 414	22	25,5	267	292	414	1		Y	Y	UN / RID/ADR				
D 292 x 440	25	26,2	267	292	440	1		Y	Y	UN / RID/ADR				
D 292 x 450	25	26,7	267	292	450	1		Y	Y	UN / RID/ADR				
D 305 x 250 L	14	15,8	285	305	250	1		Y	Y		Y		NOR, STO, S-R, TPK	
D 305 x 270 L	15	17,0	285	305	270	1		Y	Y		Y		NOR, STO, S-R, TPK	
D 305 x 285 L	16	18,1	285	305	285	1		Y	Y		Y		NOR, STO, S-R, TPK	
D 305 x 335 L	20	21,2	285	305	335	1		Y	Y		Y		NOR, STO, S-R, TPK	
D 305 x 340 L	20	21,3	285	305	340	1		Y	Y		Y		NOR, STO, S-R, TPK	
D 305 x 400 L	22	25,4	285	305	400	1		Y	Y		Y		NOR, STO, S-R, TPK	
D 305 x 417 L	25	26,8	285	305	417	1		Y	Y		Y		NOR, STO, S-R, TPK	

O - Optional

Ring types

NOR	Standard clamping ring
STO	Störing
S-R	S-Ring
TPK	TOPLock ring

Remarks:

1) UN approval with formliner available
2) Sheet thickness 0,45mm

CONICAL PAILS

Format	Filling vol. (l)	Brimful capac. (l)	Diam. bottom a) (mm)	Diam. lid b) (mm)	Height h) (mm)	Handle	Tactile	Triple seam.	Crimp lid (1)	Approval	Ring & Latch lid (2)	Approval	Ring types	Remarks
D 305 x 203	11	11,5	285	305	203	1 or 2	O	Y			Y	UN / RID/ADR	NOR, STO, S-R, TPK	
D 305 x 230	12	13,7	285	305	230	1 or 2	O	Y			Y	UN / RID/ADR	NOR, STO, S-R, TPK	
D 305 x 250	15	15,2	285	305	250	1 or 2	O	Y			Y	UN / RID/ADR	NOR, STO, S-R, TPK	
D 305 x 286	17	17,8	285	305	286	1 or 2	O	Y			Y	UN / RID/ADR	NOR, STO, S-R, TPK	
D 305 x 300	18	18,6	285	305	300	1 or 2	O	Y			Y	UN / RID/ADR	NOR, STO, S-R, TPK	
D 305 x 325	20	20,5	285	305	325	1 or 2	O	Y			Y	UN / RID/ADR	NOR, STO, S-R, TPK	
D 305 x 340	21	21,5	285	305	340	1 or 2	O	Y			Y	UN / RID/ADR	NOR, STO, S-R, TPK	
D 305 x 380	24	24,3	285	305	380	1 or 2	O	Y			Y	UN / RID/ADR	NOR, STO, S-R, TPK	
D 305 x 400	25	25,6	285	305	400	1 or 2	O	Y			Y	UN / RID/ADR	NOR, STO, S-R, TPK	
D 305 x 417	25	26,8	285	305	417	1 or 2	O	Y			Y	UN / RID/ADR	NOR, STO, S-R, TPK	
D 305 x 435	25	27,9	285	305	435	1 or 2	O	Y			Y	UN / RID/ADR	NOR, STO, S-R, TPK	
D 305 x 450	28	29,0	285	305	450	1 or 2	O	Y			Y	UN / RID/ADR	NOR, STO, S-R, TPK	
D 328 x 250	18	17,8	310	328	250	1 or 2	O	Y			Y	UN	NOR, STO, S-R, TPK	
D 328 x 290	20	21,0	310	328	290	1 or 2	O	Y			Y	UN	NOR, STO, S-R, TPK	
D 328 x 350	25	25,9	310	328	350	1 or 2	O	Y			Y	UN / RID/ADR	NOR, STO, S-R, TPK	
D 328 x 360	30	26,9	310	328	360	1 or 2	O	Y			Y	UN / RID/ADR	NOR, STO, S-R, TPK	
D 328 x 387	30	28,9	310	328	387	1 or 2	O	Y			Y	UN / RID/ADR	NOR, STO, S-R, TPK	
D 328 x 405	30	30,4	310	328	405	1 or 2	O	Y			Y	UN / RID/ADR	NOR, STO, S-R, TPK	
D 328 x 410	30	30,8	310	328	410	1 or 2	O	Y			Y	UN / RID/ADR	NOR, STO, S-R, TPK	
D 328 x 435	32	32,8	310	328	435	1 or 2	O	Y			Y	UN / RID/ADR	NOR, STO, S-R, TPK	
D 328 x 450	34	34,8	310	328	450	1 or 2	O	Y			Y	RID/ADR	NOR, STO, S-R, TPK	
D 328 x 480	35	36,5	310	328	480	1 or 2	O	Y			Y	RID/ADR	NOR, STO, S-R, TPK	
D 328 x 500	40	38,0	310	328	500	1 or 2	O	Y			Y	RID/ADR	NOR, STO, S-R, TPK	

O - Optional

Ring types

NOR	Standard clamping ring
STO	Störing
S-R	S-Ring
TPK	TOPLock ring

Remarks:

1) UN approval with formliner available
2) Sheet thickness 0,45mm